

PARTNER

CARE . TRUST . RESPONSIBILITY

CD-7220

CD-7220 Customer Display



The CD-7220 is a top quality customer display in telescope style. The vacuum fluorescence display ensures pin-sharp character definition. The display retains its optimum legibility even in brightly lit environments.

The display can also optionally draw power from a printer, making it independent of a separate power supply unit.

The CD-7220 is adjustable in height and can be matched to the requirements of any working environment.

Special Features

Vacuum fluorescence display

270° rotation option

Interface RS232 or USB

Adjustable height

Two-line display with 20 characters per line

Options

External power supply 12V

Customer Display CD-7220



Technical Data

Model	CD-7220
Display Method	Vacuum fluorescent
Display Colour	Blue green
Brightness	700 cd/m ²
Interface	RS-232 Serial (D-Sub 9pin) With pass through function, USB with 5V power (do not require power supply)
Power supply	12V
Power Consumption	5 Watt / 8 Watt
MTBF	25.000 hours
Viewable Angle	+/- 15° C
Rotation Angle	Max 270° C
Character Front	5 x7 dot matrix, Comma and decimal point
Character Size	9.0 mm x 5.25 mm
Character Front	96 alphanumerical, 13 sets and one variable
Number of Characters	40 (20 columns x 2 rows) 40 (20 columns x 2 rows) x 2 sides
Dimension	109 mm Base or 42 mm VFD (L) x 230 mm (W) max. 504 mm (H) with long & short pole
Options	Dual Side Display

