

K7



Features

- Quad-core processor, Android 7.0(MTK6737) operating system
- 4.0-inch screen, operation with Capacitive touch screen
- 4G&3G&2G Cellular,WIFI, Bluetooth
- Up to IP65 level of dustproof and waterproof
- GPS global positioning system to ensure business tracking at any time
- 4000mAh high-capacity battery,continuous work over 12 hours
- 1D or 2D barcode scanning
- Rich supporting accessories, Bluetooth printer and desktop standing charger

Product	K7	
General	Processor	MTK6737 Quad core Cortex-A53 1.3GHz
	GPU	Mali-T720
	RAM+ROM	1GB+8GB
	RAM+ROM	2GB+16GB(optional)
	Extensive SD card	32GB
	Display	4.0 inch WVGA,480*800,capacitive screen
	Camera	8M pixel,Automatic Focus,LED Flash
	Audio	Mic,Speaker,3.5mm earphone
	OS	Android 7.0
	GPS	Supports GPS,GALILEO,GLONASS and BEIDOU



HANGZHOU KAILI COMMUNICATION CO.,LTD

12 Floor, CONBA Building, Jiangnan Avenue No.288, Binjiang District. Hangzhou, China

		Supports AGPS
Scanning Engine	1D Scanning Engine (optional)	<p>Scan rate: 100±10scans/s</p> <p>Scan Angle (skew, pitch, roll) : ±50° ,±65° ,±35°</p> <p>Optical Resolution: 4mil</p> <p>Depth of Field (15mil Code39) : 45mm-350mm</p> <p>Decode capability: UPC-A, UPC-E, EAN-13, EAN-8, ISBN/ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Codabar (NW7), Code 128, Code 93, Code 11(USD-8), MSI/Plessey, UK/Plessey, UCC/EAN 128, China Post, GS1 DataBar (formerly RSS) variants</p>
	2D Scanning Engine (optional)	<p>Scan Angle (skew,pitch,roll) : ±60° ,±60° ,360°</p> <p>Optical Resolution: 5mil(Code39),5mil(PDF417)</p> <p>Depth of Field (10mil Data Matrix) : 7.4cm-25.7cm</p> <p>Decode capability: UPC/EAN/JAN,Code 39, Code 128, Code 32, Code 93, Codabar PDF417,Date Matrix,QR Code, Micro QR Code,Han Xin Code</p>
Network	WAN	<p>LTE FDD Band 1: Operating frequency range: 1920-1980, 2110-2170 MHz; Maximum output power: 23 dBm rated</p> <p>LTE FDD Band 3: Operating frequency range: 1710-1785, 1805-1880 MHz; Maximum output power: 23 dBm rated</p> <p>LTE TDD Band 38: Operating frequency range: 2570-2620 MHz; Maximum output power: 23 dBm rated</p> <p>LTE TDD Band 39: Operating frequency range: 1880-1920 MHz; Maximum output power: 23 dBm rated</p> <p>LTE TDD Band 40: Operating frequency range: 2300-2400 MHz; Maximum output power: 23 dBm rated</p> <p>LTE TDD Band 41: Operating frequency range: 2496-2690 MHz; Maximum output power: 23 dBm rated</p> <p>WCDMA Band I: Operating frequency range: 1920-1980, 2110-2170 MHz; Maximum output power: 24 dBm rated</p> <p>WCDMA Band VIII:</p>



HANGZHOU KAILI COMMUNICATION CO.,LTD

12 Floor, CONBA Building, Jiangnan Avenue No.288, Binjiang District. Hangzhou, China

		Operating frequency range: 880-915, 925-960 MHz; Maximum output power: 24 dBm rated GSM 900: Operating frequency range: 880-915, 925-960 MHz; Maximum output power: 33 dBm rated GSM 1800: Operating frequency range: 1710-1785, 1805-1880 MHz; Maximum output power: 30 dBm rated TD-SCDMA(B34,B39); CDMA EV-DO Rev.A(BC0); GPRS/EDGE(B2,B3,B5,B8)
	WLAN	IEEE 802.11b/g/n (20/40 MHz) Operating frequency range: 2412-2472 MHz (13/9 channels); Maximum output power: 17.22 dBm EIRP average (calculated); Maximum antenna gain: 2 dBi IEEE 802.11a/n (20/40 MHz) Operating frequency range: 5745-5825 MHz (5/2 channels); Maximum output power: 11.02 dBm EIRP average (calculated); Maximum antenna gain: 2 dBi
	Bluetooth	V2.1+EDR, V3.0+HS and V4.1+HS compliant
	NFC	HF 13.56MHz, Readable distance: 2-5cm ISO14443A/B,ISO15693
	SIM Card Slot	Micro SIM Card *2
Power Supply	Battery	PDA:3.7V 4000mAH Handle grip:4000mAh (optional)
	Consumption	<2W
	Standby Time	>100 Hour (PDA)
	Power	Input:110-240V AC,50/60Hz,output:5.0V DC
Certification	Safe certificate	CCC, Network access license, CE
	Protection certificate	IP65
Environmental	Operation Temperature	-20℃~55℃
	Storage Condition	-20℃~70℃
	Operation Humidity	20%~85%RH
	Ambient Illumination	0—10000Lux
Accessories	USB cable	Default
	Battery charger	Default
	Hand band	Default
	Tool package	Optional
	Cradle charger (2 in 1)	Optional
Appearance	Dimensions	185*68*37.5mm (L*W*H)
	Weight	300g (including battery)